

REV.
C

AS1734

FEDERAL SUPPLY CLASS
4730

RATIONALE

THIS DOCUMENT HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE 5-YEAR REVIEW POLICY.





FIGURE 1 - NUT

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3A

PROCUREMENT SPECIFICATION: /3/ /11/ AS1730

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

NUT, COUPLING, RIGID, FIXED CAVITY, THREADED,
FERRULE TYPE TUBE ENDS, TYPE I

AS1734
SHEET 1 OF 3

**REV.
C**

Copyright 2007 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)

Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1984-01 REVISED 1995-09 REAFFIRMED 2007-09

AS1734		REV. C
--------	--	-----------

TABLE 1 - NUT DIMENSIONS AND WEIGHTS													
BASIC NO. AS1734 SIZE CODE	(TUBE SIZE)	THREAD T PER FED-STD-H28/2	A + .010/- .000	B + .010/- .000	C + .005/- .000	D DIA	D TOL	E MAX	F	G + .010/- .000	H	WEIGHT LB/EA MAX	
04	.250	.687-12 UN-2B	.787	.691	.529	.583	+ .002/- .000	.829	.408	.338	.300	.008	
05	.312	.750-12 UN-2B	.850	.753	.580	.644	+ .002/- .000	.892	.408	.338	.300	.009	
06	.375	.812-12 UN-2B	.912	.816	.635	.689	+ .002/- .000	.954	.408	.338	.300	.010	
08	.500	.937-12 UN-2B	1.037	.941	.762	.815	+ .003/- .000	1.079	.408	.338	.300	.012	
10	.625	1.062-12 UN-2B	1.172	1.066	.900	.960	+ .003/- .000	1.214	.424	.354	.315	.013	
12	.750	1.250-12 UNF-2B	1.360	1.253	1.033	1.128	+ .003/- .000	1.402	.424	.354	.315	.015	
16	1.000	1.500-12 UNF-2B	1.610	1.503	1.284	1.386	+ .003/- .000	1.652	.424	.354	.315	.019	
20	1.250	1.750-12 UN-2B	1.860	1.753	1.534	1.628	+ .003/- .000	1.902	.484	.414	.375	.026	
24	1.500	2.000-12 UN-2B	2.110	2.003	1.783	1.878	+ .003/- .000	2.152	.499	.429	.375	.028	
28	1.750	2.250-12 UN-2B	2.360	2.253	2.045	2.138	+ .003/- .000	2.402	.499	.429	.375	.035	
32	2.000	2.500-12 UN-2B	2.620	2.503	2.292	2.382	+ .003/- .000	2.662	.499	.429	.375	.041	
36	2.250	2.750-12 UN-2B	2.870	2.753	2.549	2.638	+ .003/- .000	2.912	.560	.455	.392	.052	
40	2.500	3.000-12 UN-2B	3.125	3.003	2.800	2.889	+ .003/- .000	3.162	.560	.455	.392	.057	
44	2.750	3.250-12 UN-2B	3.370	3.253	3.045	3.138	+ .003/- .000	3.412	.560	.455	.392	.060	
48	3.000	3.625-12 UN-2B	3.751	3.628	3.395	3.513	+ .004/- .000	3.793	.560	.455	.392	.080	
56	3.500	4.125-12 UN-2B	4.256	4.128	3.895	4.013	+ .004/- .000	4.298	.560	.455	.392	.090	
64	4.000	4.625-12 UN-2B	4.756	4.613	4.395	4.513	+ .004/- .000	4.798	.560	.455	.392	.133	
72	4.500	5.125-12 UN-2B	5.266	5.113	4.895	5.015	+ .005/- .000	5.308	.678	.543	.475	.186	
80	5.000	5.625-12 UN-2B	5.765	5.613	5.378	5.500	+ .005/- .000	5.807	.678	.543	.475	.211	

	AEROSPACE STANDARD	AS1734 SHEET 2 OF 3	REV. C
	NUT, COUPLING, RIGID, FIXED CAVITY, THREADED, FERRULE TYPE TUBE ENDS, TYPE I		