

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS21940

FEDERAL SUPPLY CLASS
4730

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS21940D AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS21940D. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as21940

THIRD ANGLE PROJECTION



ISSUED 2000-09 REAFFIRMED 2004-04

PREPARED BY SAE COMMITTEE G-3


PROCUREMENT SPECIFICATION: MIL-F-18280

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

BOLT, CLUSTER FITTING, DOUBLE PORT,
FLARELESS

AS21940
SHEET 1 OF 3



LOW FLOW SIZE DASH NUMBER	TUBE OD	THREAD S MIL-S-8879	THREAD T MIL-S-8879	A REF	B	C ±.062	D +.000 -.015	E ±.062	F ±.003	H HEX	WT LB MAX
-3L	3/16	.3750-24 UNJF-3A	.4375-20 UNJF-3A	2.531	3.265	---	.621	2.568	.125	.621 .628	.020
-4L	1/4	.4375-20 UNJF-3A	.4375-20 UNJF-3A		3.328	---	.684	2.653	.187	.684 .691	
-5L	5/16	.5000-20 UNJF-3A	.4375-20 UNJF-3A		3.390	---	.746	2.715	.234	.746 .753	
-6L	3/8	.5625-18 UNJF-3A	.4375-20 UNJF-3A		3.437	.663	.871	2.725		.871 .878	
-8L	1/2	.7500-16 UNJF-3A	.4375-20 UNJF-3A		3.530	.656	.996	2.780		.996 1.003	
HIGH FLOW SIZE DASH NUMBER	TUBE OD	THREAD S MIL-S-8879	THREAD T MIL-S-8879	A REF	B	C ±.062	D +.000 -.015	E ±.062	F ±.003	H HEX	WT LB MAX
-6H	3/8	.5625-18 UNJF-3A	.5625-18 UNJF-3A	2.969	3.875	---	.871	3.162	.297	.871 .878	.050
-8H	1/2	.7500-16 UNJF-3A	.5625-18 UNJF-3A		3.968	---	.996	3.218		.996 1.003	
-10H	5/8	.8750-14 UNJF-3A	.5625-18 UNJF-3A		4.031	.812	1.121	3.242	.422	1.121 1.128	

REQUIREMENTS:

1. MATERIAL: ALUMINUM ALLOY - BARS. SEE PROCUREMENT SPECIFICATION.
2. FINISH: SEE PROCUREMENT SPECIFICATION.
SURFACE FINISH IN ACCORDANCE WITH ANSI B46.1.
ALL OUTSIDE MACHINED SURFACES 125 MICROINCHES Ra. ALL INSIDE 250 Ra UNLESS OTHERWISE NOTED.

NOTES:

1. FITTINGS SHALL BE FREE FROM ALL HANGING BURRS AND SLIVERS.
2. DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMAL ± 0.010 , ANGLES $\pm 1/2^\circ$.
3. PART NUMBERS:

NO CODE LETTER IN PART NUMBER FOR ALUMINUM ALLOY (2024).
ADD "W" IN PLACE OF DASH FOR ALUMINUM ALLOY (7075).

EXAMPLES OF PART NUMBERS:

MS21940-8L - BOLT, 1/2 TUBING, LOW FLOW, ALUMINUM ALLOY (2024).
MS21940W8L - BOLT, 1/2 TUBING, LOW FLOW, ALUMINUM ALLOY (7075).

4. INSTALLATION IN ACCORDANCE WITH MS21931.