

REV.
B

AS4231

FEDERAL SUPPLY CLASS
4730

RATIONALE

TO CORRECT THE DEFINED LEG DIAMETER DIM G.





FIGURE 1: FITTING, ELBOW, 45°, BULKHEAD

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3B

PROCUREMENT SPECIFICATION: /5/ AS4510

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

FITTING, ELBOW, 45°, BULKHEAD, EXTERNAL
THREAD, BEAM SEAL TO INTEGRAL WELD RING

AS4231
SHEET 1 OF 4

**REV.
B**

TABLE 1A - DIMENSIONS

BASIC NO. AS4231 /16/ SIZE AND TUBE WALL CODES	RANGE OF NOMINAL TUBE WALL FOR PORT #2 /7/ /16/	(NOMINAL TUBE SIZE)	PORT #1 STYLE /10/	T THREAD PER AS8879 CLASS 3A	A	B	C	D /10/
03-018	.016-.018	.188	A	.3750-28 UNJS	.832	.987	.610	.146
03-022	.019-.022	.188	A	.3750-28 UNJS	.832	.987	.610	.138
04-022	.019-.022	.250	B	.4375-24 UNJS	.832	1.028	.680	.200
05-022	.019-.022	.312	B	.5000-24 UNJS	.887	1.046	.650	.262
05-028	.023-.028	.312	B	.5000-24 UNJS	.887	1.046	.650	.250
06-022	.019-.022	.375	B	.5625-20 UNJS	1.005	1.120	.740	.325
06-028	.023-.028	.375	B	.5625-20 UNJS	1.005	1.120	.740	.313
06-032	.029-.032	.375	B	.5625-20 UNJS	1.005	1.120	.740	.305
08-022	.019-.022	.500	B	.7188-20 UNJS	1.180	1.246	.820	.450
08-043	.033-.043	.500	B	.7188-20 UNJS	1.180	1.246	.820	.408
10-028	.023-.028	.625	B	.8438-18 UNJS	1.243	1.433	.880	.563
10-043	.033-.043	.625	B	.8438-18 UNJS	1.243	1.433	.880	.533
10-055	.044-.055	.625	A	.8438-18 UNJS	1.243	1.433	.880	.509
12-028	.023-.028	.750	B	1.0000-16 UNJ	1.392	1.576	.980	.688
12-055	.044-.055	.750	A	1.0000-16 UNJ	1.392	1.576	.980	.634
12-065	.056-.065	.750	A	1.0000-16 UNJ	1.392	1.576	.980	.614
14-032	.029-.032	.875	B	1.1250-16 UNJ	1.562	1.725	1.090	.805
14-065	.056-.065	.875	A	1.1250-16 UNJ	1.562	1.725	1.090	.739
16-043	.033-.043	1.000	B	1.2500-14 UNJS	1.617	1.725	1.150	.908
16-078	.066-.078	1.000	A	1.2500-14 UNJS	1.617	1.725	1.150	.838
16-089	.079-.089	1.000	A	1.2500-14 UNJS	1.617	1.725	1.150	.816
20-055	.044-.055	1.250	B	1.5781-14 UNJS	1.750	1.775	1.170	1.134
20-089	.079-.089	1.250	A	1.5781-14 UNJS	1.750	1.775	1.170	1.066
24-055	.044-.055	1.500	B	1.8438-14 UNJS	1.900	2.027	1.270	1.384

TABLE 1B - DIMENSIONS AND WEIGHTS

BASIC NO. AS4231 /16/ SIZE AND TUBE WALL CODES	E /10/	F ±.005	G MIN	V	W	RECOMMENDED MAXIMUM PRESSURE PSI /7/	LB/EA MAX CRES	LB/EA MAX TI
03-018	--	.080	.285	.360- .377	.055	5000	.0369	.0211
03-022	--	.080	.285	.360- .377	.055	5000	.0369	.0211
04-022	.184- .194	.080	.329	.360- .377	.060	5000	.0461	.0263
05-022	.232- .242	.080	.391	.423- .440	.060	4000	.0630	.0360
05-028	.232- .242	.080	.391	.423- .440	.060	5000	.0630	.0360
06-022	.297- .307	.090	.454	.485- .502	.060	3000	.0790	.0452
06-028	.297- .307	.090	.454	.485- .502	.060	4000	.0790	.0452
06-032	.297- .307	.090	.454	.485- .502	.060	5000	.0790	.0452
08-022	.398- .408	.090	.575	.547- .565	.065	2000	.132	.0753
08-043	.398- .408	.090	.575	.547- .565	.065	5000	.132	.0753
10-028	.512- .523	.125	.673	.673- .691	.070	2000	.188	.107
10-043	.512- .523	.125	.673	.673- .691	.070	4000	.188	.107
10-055	--	.125	.673	.673- .691	.070	5000	.188	.107
12-028	.649- .660	.125	.880	.860- .878	.095	2000	.275	.157
12-055	--	.125	.880	.860- .878	.095	4000	.275	.157
12-065	--	.125	.880	.860- .878	.095	5000	.275	.157
14-032	.769- .780	.125	1.135	1.110-1.128	.105	2000	.425	.243
14-065	--	.125	1.135	1.110-1.128	.105	4000	.425	.243
16-043	.862- .874	.125	1.135	1.110-1.128	.110	2000	.480	.274
16-078	--	.125	1.135	1.110-1.128	.110	4000	.480	.274
16-089	--	.125	1.135	1.110-1.128	.110	5000	.480	.274
20-055	1.115-1.128	.180	1.405	1.355-1.380	.110	2000	.718	.410
20-089	--	.180	1.405	1.355-1.380	.110	4000	.718	.410
24-055	1.324-1.337	.180	1.665	1.605-1.630	.130	2000	1.120	.640

NOTES:

/1/ MATERIAL:

- a. CODE LETTER T - TYPE 6AL-4V TITANIUM ALLOY FORGING OR BAR PER AMS 4965.
- b. CODE LETTER P - TYPE 17-4PH CORROSION RESISTANT STEEL FORGING OR BAR PER AMS 5643.
- c. CODE LETTER V - TYPE 15-5PH CORROSION RESISTANT STEEL FORGING OR BAR PER AMS 5659.

2. HEAT TREATMENT:

- a. MATERIAL CODE LETTER T - NONE.
- b. MATERIAL CODE LETTERS P AND V - HEAT TREAT TO CONDITION H 1075 PER AMS 2759/3.

3. FINISH:

- a. MATERIAL CODE LETTER T - NONE.
- b. MATERIAL CODE LETTER P AND V - PASSIVATE PER AMS 2700.