



SURFACE VEHICLE INFORMATION REPORT

SAE**J1299 FEB2013**Issued 1982-08
Stabilized 2013-02

Superseding J1299 SEP2003

Electrical Propulsion Control - Off-Road Dumpers

RATIONALE

The content of this standard is becoming obsolete, and there is no longer support to update this standard. The Con-Ag effort is supporting the creation of ISO 14990, which should supersede SAE J1299 in about 2 years.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE CTTC C2, Electrical Components and Systems Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of J1299_201302

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J1299_201302**

Foreword—This Document has also changed to comply with the new SAE Technical Standards Board Format.

1. **Scope**—This SAE Information Report applies to the control circuits and devices associated with the electrical propulsion system used on electric drive dumpers. Dumper is defined in J/ISO 6165. The document does not apply to auxiliary equipment control systems such as:

- a. Battery charging systems
- b. Engine wiring and control
- c. Monitoring and control circuits not directly affecting the operation of the electric propulsion and retarding system
- d. Lighting
- e. Accessory systems (heating, air conditioning, horns, radios, emergency steering, fire protection, and similar functions).

1.1 **Purpose**—This document establishes requirements for the control circuits and control devices of the electric propulsion system of an electric drive dumper. Criteria are established for environmental service conditions, control systems requirements, control device operational requirements and control tests.

2. **References**

2.1 **Applicable Publications**—The following publications form a part of the specification to the extent specified herein. Unless otherwise indicated, the latest revision of SAE publications shall apply.

2.1.1 SAE PUBLICATIONS—Available from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096-0001

SAE J/ISO 6165 MAY99—Earthmoving Machinery - Basic Types - Vocabulary

SAENORM.COM : Click to view the full PDF of J1299-201302

3. *Definition of Terms*

3.1 Dynamic Retarding—A method of slowing the dumper, or controlling its speed downgrade, by the controlled conversion of the dumper's kinetic energy to electrical power. A commonly used method is to dissipate this electrical power as heat through retarding resistors. These resistors may be:

- a. Natural convection retarding resistors which dissipate heat to air circulated through the resistors by natural convection; or
- b. Forced convection retarding resistors which dissipate heat to air forced through the resistors by a blower or fan.

3.2 Extended Range Retarding—The shunting out of a portion of the retarding resistors to maintain a high level of dynamic retarding effort at low dumper speeds.

3.3 Overspeed Retarding—The automatic application of dynamic retarding at, or above, a selected dumper speed.

3.4 Routine Tests—Tests carried out on all electromechanical control devices and electronic assemblies prior to shipping by the supplier.

3.5 Type Tests—Tests carried out on one or more electromechanical control devices and electronic assemblies of a new or modified functional design to determine conformance to design requirements.

3.6 U—Represents rated value of supply voltage (nominal voltage).

4. Service Conditions—The control shall perform within the design limits at altitudes up to 3000 m above sea level and at ambient temperatures between -40 and $+50$ °C.

Special arrangements shall be agreed upon between user and manufacturer to cover the case of service conditions more severe than those mentioned above.

5. *Control System*

5.1 Main Control Enclosure—When locating and/or constructing the main control enclosure, malfunctions due to the environment, dust, material spillage, fluid leakage, and/or rejected heat from other equipment shall be considered.

Equipment should be accessible for service, monitoring, and/or replacement.

5.2 Arrangement of Equipment—Components within the enclosure should be arranged in groups corresponding to voltage level of the circuit which they control. For example:

- a. Traction power and retarding transmission systems
- b. Excitation systems
- c. Control systems

Individual components shall be identified indicating their function within the system. The designation shall be readily visible on, or closely adjacent to, the component.

- 5.3 Operator's Controls**—Both propel and retarding mode selection and modulation should be foot operated except in the special application of trolley assist.

Dumper direction control should be hand operated and shall, in addition to forward and reverse, include a neutral position.

Voltage in excess of 100 V shall not be used on the operator's controls.

- 5.4 Circuit Requirements**—The circuitry to accomplish the retarding function shall not be disabled by equipment protection devices unless provided with an override either automatic or accessible to the operator while driving.

The circuitry shall provide for the override of the propel function by the retarding function. Otherwise, except as may be required for the braking systems, the propel function shall be completely under the manual control of the operator at all times. If the propel function is disabled when the service brakes are applied, a manual override of this disable feature shall provide for forward operation of the dumper. The propel function shall not be latched except in the special applications of trolley assist. This paragraph does not apply to remote controlled dumpers.

The transition time between the propel and retarding functions shall not exceed 8 s and is preferably less than 4 s.

Alarm systems which indicate equipment failures for the operator shall have indicators which can be heard and/or seen while operating the dumper.

The circuit shall ensure that there shall be no torque output from the traction motors with the direction control in neutral or with the direction control in forward or reverse and propel control not actuated.

Automatic overspeed retarding shall be provided.

Provision may be made for extended range retarding for applications which require additional retarding at low speed.

On rear dumpers, the reverse propel function shall be disabled during dumping.

If the forward propel function is disabled during the dumping function, a manual override of this disable feature shall provide for forward operation of the dumper.

6. Control Devices

- 6.1 Power Conditioning Devices**—Devices used to convert AC power to DC power and to control DC power shall be mounted in such a way so as to be accessible for inspection and/or replacement.

- 6.2 Retarding Resistors**—The resistors shall be located on the dumper such that their rejected heat will not damage other equipment.

The time-current rating of the resistors, as qualified by the degree of ventilation provided, shall be available from the manufacturer.

- 6.3 Temperature Rise Limits**—The temperature rise limits of insulated windings and control devices shall be such as to provide a minimum service life of 50 000 engine hours. Service life is that service time period resulting in 50% of the windings or control devices still being functional.

6.4 Limits in Variation of Supply Air Pressure—When apparatus is pneumatically or electropneumatically operated, it shall function satisfactorily at an air pressure of 50% through 110% of the regulated pressure setting.

6.5 Limits of Variation of Supply Voltage—The electrical, electronic, electropneumatic, or electromagnetic equipment shall operate satisfactorily at any value of supply voltage between 75% and 110% of the rated value.

7. Control Device Test

7.1 Categories of Tests—There are two categories of tests:

- a. Routine tests (see 3.4)
- b. Type tests (see 3.5)

7.2 Lists of Tests—The principal tests to be carried out on control devices prior to installation on dumper are set out in Table 1, together with the clause numbers to which reference should be made.

TABLE 1—LIST OF TESTS

Nature of Test	Type Test	Routine Test
1. Mechanical Test for Control Devices		
Mechanical Operation (Limits of Variation)	7.4.1	7.4.2
Mechanical Endurance (Life)	7.5	
Vibration and Shock (Strength)	7.6	
2. Electrical Test for Control Devices		
Measurement of Resistance and Impedance		7.7
Temperature Rise Test	7.8	
Breaking and Making Capacities Test	7.9	
Component Dielectric Test		7.10
Voltage Transient Susceptibility of Electronic Assemblies	7.11	

7.3 Measurement Accuracy—The error of measurement techniques shall be less than 5% of the quantity measured, unless otherwise specified. Temperature measurement accuracy shall be ± 2 °C.

7.4 Mechanical Operation Tests—This section describes type tests and routine tests for electro-mechanical and electro-pneumatic control devices.

7.4.1 MECHANICAL OPERATION TYPE TEST—Type test shall be carried out at both the lowest and highest ambient temperature as defined in Section 4 with the devices at temperature stabilized condition. These tests consist of operating twenty times in succession, for each combination, to verify that the apparatus will operate correctly within the limits of air pressure and supply voltage specified in 6.4 and 6.5.

7.4.1.1 A test shall also be made to verify that the operation of the equipment is still satisfactory when carried out under the most unfavorable combination of temperature, air pressure, and voltage obtainable within the limits specified in 6.3, 6.4, and 6.5.

- 7.4.2 MECHANICAL OPERATION ROUTINE TESTS—Routine tests consist of one actuation only of the tests described in 6.4.1 at local ambient temperature only.

NOTE—In the case of electromagnetic or electropneumatic apparatus, operation shall be considered to be satisfactory if the apparatus operates normally when it is supplied with 75% of rated voltage.

- 7.5 **Tests for Mechanical Endurance**—These are type tests for mechanical endurance of electromechanical and electropneumatic control devices which shall be made at the rated regulated supply voltage of the control circuit and at the rated air pressure for apparatus with electropneumatic control, the apparatus operating at no-load. These tests are as follows:

- a. 2 000 000 cycles minimum for contactors and relays used in the main power transmission (which includes retarding) system.
- b. 750 000 cycles minimum for reversers.
- c. 20 000 cycles minimum for all other devices.

- 7.5.1 MECHANICAL ENDURANCE TESTS SHALL BE CARRIED OUT

- a. At a rate consistent with the minimum cycle time of the control device.
- b. With the control device mounted in a manner consistent with its normal application.
- c. With a method of lubrication consistent with recommended preventive maintenance practices.

The apparatus shall be considered as having successfully passed the mechanical endurance tests if, after the tests, they are capable of operating normally without special attention, other than cleaning and lubrication.

- 7.6 **Test for Withstanding Vibration and Shock for Control Devices**—These tests are type tests to be carried out on all control devices. The control device is secured in a suitable position to a machine producing vibrations of sinusoidal form with adjustable amplitude and frequency and is then subjected to the following tests. The test is carried out successively in each of the three directions: vertical, longitudinal, and transverse.

- 7.6.1 THE DETERMINATION OF RESONANT FREQUENCIES—To determine the possible existence of critical frequencies producing resonance, the frequency shall be varied progressively between 1 and 50 Hz with the displacement (a), expressed in millimeters given as a function of frequency (f), in the equation:

$$a = 14e^{-f/11.2} \quad (e = 2.718, \dots) \quad (\text{Eq. 1})$$

If resonance is produced, the corresponding frequency shall be maintained and the device monitored for change of state per 7.6.2.

- 7.6.2 TEST WITH SUSTAINED VIBRATION—The control device, at no-load, is subjected to a test with sustained vibration for a period of 4 h:

- a. Either at the critical frequency, if any such well defined frequency has been detected in the course of the test of 7.6.1,
- b. Otherwise, at a frequency of 10 Hz.

In the case of relays, circuit-breaking equipment, etc., the test is carried out during the first and second hours in the "open" position; and in the third and fourth hours in the "closed" position.

The test is considered to be satisfactory if there is no resulting damage or abnormality in operation.

- 7.6.3 TESTS TO SIMULATE THE EFFECT OF SHOCKS—The de-energized control device is to be subjected to three successive shocks to the base of the device in each of three directions (vertical, longitudinal, and transverse) with an acceleration of at least 10 g of 11 ms duration per shock.

If the device is designed for mounting on shock absorbing devices, these shall be in place during the test.

The test is considered to be satisfactory if there is no resulting malfunction or abnormality in operation.

- 7.7 **Measurement of Resistance and Impedance**—These are routine tests made on all electropneumatic or electromagnetic control device windings when cold.

The measurement obtained for any given winding, when corrected to a temperature of 20 °C, shall not vary by more than ±10% from the specified value or, alternatively, from the mean of the values measured on the first ten units tested.

The measurements of resistance are also made when cold on the various resistances inserted in the power transmission control circuits. The allowable tolerances which vary according to the application shall be agreed upon between the parties concerned.

For apparatus in AC circuits or in DC circuits where correct operation depends on the impedance, measurements of impedance shall be carried out with AC at the specified frequency.

The following relationship should be used to correct resistance measurements to 20 °C;

$$\frac{R_1}{R_2} = \frac{T_1 + 234.5}{T_2 + 234.5} \rightarrow R_1 = R_2 \frac{(254.5)}{(T_1 - 234.5)} \quad (\text{Eq. 2})$$

Where:

R1 (ohms) and T1 (°C) are values at 20 °C
R2 (ohms) and T2 (°C) are actual values measured

7.8 Temperature Rise Tests

- 7.8.1 GENERAL—These are type tests. They are applied to constituent parts of equipment: windings, blow-out coils, main contacts, flexible connections, and regulating and protective resistances.

The apparatus to be tested shall be mounted so as to reproduce approximately the normal service conditions on the dumper, particularly with regard to ventilation. For apparatus ventilated by dumper motion, artificial ventilation reproducing conditions similar to those encountered in service may be applied.

Each test shall be carried out for a period of time sufficient to enable the temperature rise to reach a steady-state value. In practice, this condition is fulfilled when the temperature variation does not exceed 5 °C per hour.

- 7.8.2 INSULATED WINDINGS—Temperature tests on insulated windings shall be made at the continuous rated voltage.
- 7.8.3 BARE WINDINGS, MAIN CONTACTS, AND FLEXIBLE CONNECTIONS—Temperature-rise tests on blow-out coils, the windings of relays constructed of a single layer of heavy section turns, contact tips and their flexible connections are to be carried out with continuous rated current.