



SURFACE VEHICLE STANDARD	J1360	AUG2013
	Issued	1981-06
	Revised	2013-08-08
Superseding J1360 FEB2006		
Product Identification Numbering System of Off-Road Work Machines		

RATIONALE

This standard has been revised to update the referenced standard for Agricultural Tractors.

1. SCOPE

This standard covers self-propelled off-road work machines as categorized in SAE J1116 and Agricultural Tractors as defined in ANSI/SAE S390.

1.1 Purpose

This standard has been established for the development and implementation of a product identification numbering system.

For an alternative product numbering system for earth-moving machines, see ISO 10261.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J1116 Categories of Off-Road Self-Propelled Work Machines

2.1.2 ISO Publications

Available from American National Standards Institute, 25 West 43rd Street, New York, NY 10036-8002, Tel: 212-642-4900, www.ansi.org.

ISO 10261 Earth-moving machinery - Product identification numbering system

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J1360_201308**

2.1.3 ASABE Publication

Available from ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659. Tel: 269-428-6324, www.asabe.org.

ANSI/SAE S390 Definitions and Classifications of Agricultural Field Equipment

3. DEFINITIONS

3.1 PRODUCT IDENTIFICATION NUMBER (PIN)

That unique identification usually referred to as an "end-product serial number," assigned to a "complete" self-propelled off-road work machine by the manufacturer.

3.2 COMPONENT OR ATTACHMENT SERIAL NUMBER

That unique serial number assigned by a manufacturer for identification purposes to certain major components (axle, engine, transmission, etc.) or to attachments (backhoe, ripper, loader, ROPS, winch, etc.) used in self-propelled off-road work machines. Rather than assigning a unique serial number, the component or attachment serial number may be the same as, or a derivative of, the PIN.

3.3 CONCEALED PRODUCT IDENTIFICATION NUMBER

The PIN placed on the machine in a concealed location that is the same unique number described in paragraph 3.1 or a derivative of that number.

3.4 LABEL

Means of displaying a PIN or component/attachment serial number on the machine. For purposes of conformance to this standard, serial numbers indelibly etched or imprinted directly onto the component or attachment is considered labeling (See paragraph 6.2).

3.5 PRODUCT IDENTIFICATION NUMBER DERIVATIVE (PIN Derivative)

A number which is adopted from a given PIN and contains fewer characters. It is unique for each machine and relates to the PIN in a uniform manner. It may be affixed to machine components (or used as a Concealed Product Identification Number) to associate the component with the machine bearing the original PIN.

4. CHARACTERISTICS OF NUMBER

4.1 Length

The PIN or serial numbers on labels or stamped on the machine shall consist of at least 6 but not more than 17 characters and may consist of Arabic numerals and Roman letters. Manufacturers should strive for a uniform format and number of characters within their company.

The numeral zero (0) shall be used to fill out the leading positions of the number whenever less than 6 characters are used. As an example, the numeral "101" shall read "000101," "0000101," etc.; "AF3" shall read "000AF3," "0000AF3," etc. All documentation and/or ownership information shall record the number with the leading zero(s).

The PIN or serial number shall be displayed in one horizontal line without breaks or separations.

4.2 Characters

Only the following Arabic numerals and Roman letters shall be used in the PIN or serial numbers:

Arabic numerals: 1 2 3 4 5 6 7 8 9 0

Roman letters: A through Z, except for I O Q

4.3 Significance of Characters

The manufacturer may attach significance to the meaning of any numeral or letter assigned to a PIN or serial number.

4.4 Duplication

A manufacturer shall ensure that non-duplicative PIN's are used and that the same PIN is not re-issued for thirty (30) years within the manufacturer's company.

5. OWNER-APPLIED NUMBERS

This standard is not intended to cover various systems of owner-applied identification numbers. The owner-applied number is not intended to be a manufacturer's PIN or serial number.

6. DISPLAY OF PIN AND SERIAL NUMBERS

6.1 PIN Label

The many configurations of machines preclude having a standardized location for the PIN label.

The PIN label shall be located on a permanent structure of the machine not normally considered a replaceable item and which does not readily lend itself to substitution.

The preferred location of the PIN label is on the left side of the machine adjacent to the operator's access area. It shall be readable, without removing any part of the machine, under daylight lighting conditions, by an observer having 20/20 vision (Snellen).

On machines where the above is not practicable, the manufacturer shall select a location that would be considered obvious to someone looking for the PIN label.

6.2 Component and Attachment Serial Number Label

Component and attachment serial number labels shall be located on the applicable component or attachment in such a manner as to maximize visibility. Rather than using labels, the manufacturer may elect to indelibly etch or imprint the serial number directly onto the component or attachment.

The serial number label shall be located on a permanent structure of the attachment or component not normally considered a replaceable item and which does not readily lend itself to substitution.

Those components and attachments receiving a serial number shall be at the discretion of the manufacturer.

7. PROTECTION FROM ELEMENTS AND ENVIRONMENT

If possible, all labels shall be placed in such a location so as to minimize the risk of damage to the labels during machine operation or from weathering.

8. DURABILITY AND SIZE OF CHARACTERS

The PIN, the serial number, and model number (if used) shall be impressed or embossed on the label to a minimum of 0.25 mm or fabricated in a similar, durable manner. Materials shall be used that will minimize the risk of loss of label information. The characters used on labels shall have a minimum height of 4.6 mm.

9. RESISTANCE TO ALTERATION OR REMOVAL

The labels shall be constructed and affixed to the machine in such a manner so that it will be difficult to alter or remove without detection or mutilation.

10. IDENTITY OF MANUFACTURER OR IMPORTER

The label shall identify the name of the manufacturer (or in the case of imported products, the importer's name may be shown) and shall include the manufacturer's name, city, and state, including zip code. If desired, the manufacturer's logo may also be included. If the manufacturer's or importer's name does not appear in the telephone or city directory of the city indicated, the street address shall also be shown.

11. PROTECTION AGAINST ADDING CHARACTERS

A symbol shall immediately precede the first numeral or letter and immediately follow the last numeral or letter of the PIN or serial number shown on labels or stamped on the component, or placed on the machine in a concealed location. The selection of the specific symbol is at the discretion of the manufacturer but shall not be any character that may be confused with an Arabic numeral or Roman letter. The symbol may be an asterisk (*), a company logo, or other configuration.

Symbols are designed to provide protection against the likelihood of characters being added to the PIN or serial number. If the same objective is achieved by providing an appropriate site or plate design on which the PIN is affixed, symbols are not required.

12. CONCEALED PRODUCT IDENTIFICATION NUMBER

In addition, manufacturers shall indelibly etch or imprint the PIN or a Product Identification Number Derivative in a concealed location on a permanent structure of the machine which is not normally considered a replaceable or substitutable item. The Concealed Product Identification Number shall be impressed to a minimum depth of 0.2 mm. The characters used in the Concealed Product Identification Number shall have a minimum height of 6.0 mm and all characters must be legible. Protection against adding characters to the Concealed Product Identification Number shall be taken. (See Section 11 - Protection Against Adding Characters.)

The location of the Concealed Product Identification Number shall be visible without removing, detaching, or dismantling any major part of the machine (except for lightweight guards, shields, etc.)

The location of the Concealed Product Identification Number shall NOT be published in the operator's or service manual and is divulged only to authorized law enforcement officers and others on a need-to-know basis.

13. GRAPHICS FOR LABELS

The PIN, serial number, model number (if used), and manufacturer's name and address shall be prominently displayed on the label as in Figures 1 and 2.

To facilitate reading of the acronym "PIN," the first letter of each word shall be bold letters and vertical stacking of the three words "Product Identification Number" is preferred, although horizontal placement is satisfactory.

The sample labels in Figures 1 and 2 meet the spirit and intent of this SAE Recommended Practice. They are not intended to portray mandatory graphics layout for the labels except as otherwise noted.